

K1H-TPR silent



内径 Ø = d I.D. Ø = d		外径 Ø = D O.D. = D		弯曲半径 (最小值) r (min.)	重量 Weight	负荷能力 = Load Capacity		长度 Length	产品代码 Part-No.
毫米 mm	公差 Tolerance	毫米 mm	公差 Tolerance	毫米 mm	克/米 ca. g/m	负压 Vacuum 毫巴 mbar	压力 Pressure 巴 bar	米 m	
10		15,6		r = d	89	600	1,0	10m	1-1906-010-00
12		17,6			103				1-1906-012-00
14		19,6			118				1-1906-014-00
16		21,6			133				1-1906-016-00
18		23,6			148				1-1906-018-00
20		25,6			163				1-1906-020-00
25	+1 / -0	30,6	+1,5 / -0		201	550	0,9		1-1906-025-00
26		31,6			163				1-1906-026-00
30		35,6			186				1-1906-030-00
32		37,6			198				1-1906-032-00
35		40,6			215				1-1906-035-00
38		43,6			233				1-1906-038-00
40		45,6			245				1-1906-040-00
45		50,6			274				1-1906-045-00
48	+1,5 / -0	54	+2 / -0		284				1-1906-048-00
50		56			296	500	0,7		1-1906-050-00
51		57			301				1-1906-051-00
55		61			324				1-1906-055-00
60		66			353				1-1906-060-00
63		69			370				1-1906-063-00
70		76,4			470				1-1906-070-00
75	+2 / -0	81,4	+3 / -0		503				1-1906-075-00
80		87			662				1-1906-080-00
90		97			742				1-1906-090-00
100		107			823	450	0,5		1-1906-100-00
102		109			839				1-1906-102-00
110	+3 / -0	117	+4 / -0	130	903				1-1906-110-00
120		127		150	984				1-1906-120-00
125		132		175	1024				1-1906-125-00
127		134		180	1040				1-1906-127-00
130		138		180	1165	200	0,4		1-1906-130-00
140		148		185	1253				1-1906-140-00
150		158		190	1340			7m	1-1906-150-00
160		168		195	1428				1-1906-160-00
175	+4 / -0	183	+6 / -0	205	1560				1-1906-175-00
180		188		220	1604				1-1906-180-00
200		208		250	1779	150	0,2		1-1906-200-00
250	+6 / -0	258	+9 / -0	330	1941				1-1906-250-00
300		308		420	2326	100	0,15		1-1906-300-00

如需其他内径和管壁颜色，欢迎来电垂询

表中负压和压力值会随安装和工作条件而改变。如有疑问，请将应用告知我们，我们非常高兴提供建议给您。如需其他规格软管（如：其他的内径、管壁颜色和公差），欢迎来电垂询。

注：以上数据基于常温 20°C。

Stand: 08/2003

Other diameters and colours on request

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request.
Technical Data (at 20°C).