



K1Z-SS-PU

钢丝加强型软管



结构: 管壁材料: 抗微生物和水分解的聚氨酯, 硬度为邵氏 85A, 弹性钢丝螺旋加强嵌入管壁中。

特性: 重型软管, 内壁平滑, 弯曲灵活, 具高拉伸、耐磨强度和断裂延伸率。无柔软剂, 无卤, 无害, 无镉。

应用范围: 木工行业的通用管, 塑料和化学行业中固体的输送。

温度范围: -40°C - +90°C
(短时间内可达 +125°C)

颜色: 透明

备案: 备有阻燃管供选用。

Hoses – with steel wire reinforcement

Structure: Wall made of microbe and hydrolysis resistant Polyurethane, Shore A ~85 A, spring steel spiral embedded into wall.

Characteristics: Flexible and heavy hose with smooth interior and high tensile and abrasion strengths and ultimate elongation. Free of softeners, halogen free, physiological safe, cadmium free.

Applications: Universal hose for the woodworking, plastic and chemical industry for transportation of solids.

Temperature range: -40°C to +90°C
(+125°C short term)

Colour: transparent

Specialties: also in flame retardant available

内径 Ø = d		外径 Ø = D		弯曲半径 (最小值) r (min.)	重量	负荷能力		长度	产品代码
I.D. Ø = d		O.D. = D			Weight	= Load Capacity		Length	Part-No.
毫米 mm	公差 Tolerance	毫米 mm	公差 Tolerance		克/米 ca. g/m	负压 Vacuum 毫巴 mbar	压力 Pressure 巴 bar		
32	+1,5 / -0	41	+2 / -0	r = 1,2 x D	396	700	3,0	10m	4-8400-032-00
35		44			430				4-8400-035-00
38		47			465				4-8400-038-00
40		49			488				4-8400-040-00
42		52			511				4-8400-042-00
45		54			545				4-8400-045-00
48		57			580				4-8400-048-00
50		59			603				4-8400-050-00
51		60			614	600	2,5		4-8400-051-00
55		59			660				4-8400-055-00
60	69	718				4-8400-060-00			
65	74	775				4-8400-065-00			
70	79	833				4-8400-070-00			
75	84	863				4-8400-075-00			
76	+2 / -0	85	+3 / -0		874				4-8400-076-00
80		89			919	500	2,0		4-8400-080-00
83		92			953				4-8400-083-00
90		99			1031				4-8400-090-00
100	+3 / -0	110	+4 / -0		1297				4-8400-100-00
102		112			1322	420	1,5		4-8400-102-00
110		120			1423				4-8400-110-00
120		130			1550				4-8400-120-00
125		135			1613				4-8400-125-00
127		137			1638				4-8400-127-00
130		140			1676				4-8400-130-00
140		150			1802				4-8400-140-00
150	+4 / -0	160	+6 / -0		1928				4-8400-150-00
152		162			1954				4-8400-152-00
160		170			2055	330	1,0		4-8400-160-00
175		185			2244				4-8400-175-00
180		190			2307				4-8400-180-00
200		210			2503				4-8400-200-00
203		213			2598				4-8400-203-00
225	+ 6 / -0	235	+9 / -0		2876				4-8400-225-00
250		260			3192	250	0,7		4-8400-250-00
280		290			3571				4-8400-280-00
300		310			3824				4-8400-300-00
350		360			4456				4-8400-350-00

如需其他内径和管壁颜色, 欢迎来电垂询

表中负压和压力值会随安装和工作条件而改变。如有疑问, 请将应用告知我们, 我们非常高兴提供建议给您。如需其他规格软管 (如: 其他的内径、管壁颜色和公差), 欢迎来电垂询。

注: 以上数据基于常温 20°C。

Stand: 07/2003

Other diameters and colours on request

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request.
Technical Data (at 20°C).