

VSM-ES



螺纹管

结构/特性: 结构类似 VSM-E, 但是保护管间隔局部剪空, 可以看到导线。

应用范围: 用于放置多芯导线或者需要压力的导管, 质量极轻, 弯曲灵活, 容易拉伸。

温度范围: -20°C - +60°C

管壁标准色: 金属银

螺旋方向: 左手螺旋

Profile hoses

Construction/Features: As type VSM-E, but protective hose with cut out segments, helix-wise or partially intermittent.

Applications: For input of e.g. multiple core electric conduits or pressure resp. supply hoses, very light, highly flexible.

Temperature: - 20 °C - + 60 °C

Colour: silver-metallic

Spiral pitch: left-hand

Innen Ø = d		Außen Ø = D		r (mind.)	Gewicht	Wendelsteigung		Fertigungs- länge	Bestell-Nr.
I.D. Ø = d		O.D. Ø = D		r (min.)	Weight	Spiral pitch		Length	Part-No.
mm	Toleranz Tolerance	mm	Toleranz Tolerance	mm	≈ g/m	mm	Toleranz Tolerance	m	
32	±0,5	40	±0,7	60	300	5	+0,2	*	74 3925 032 000

*auf Anfrage

*on request

如需其他内径和管壁颜色, 欢迎来电垂询

Other diameters and colours on request

Je nach Einbau- oder Betriebsverhältnissen können die Vakuum- bzw. Druckwerte von der Tabelle abweichen. Bitte schildern Sie uns im Zweifelsfall Ihren Einsatz, wir beraten sie gern. Zwischengrößen, andere Längen und Farben, abweichende Toleranzen etc. sind nach Vereinbarung lieferbar.
Technische Werte (bei +20°C).

Stand: 04/2003

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request.
Technical Data (at 20°C).