

VSM



螺纹管

结构: EVA 材质

特性: 全塑料波纹管, 内壁平滑, 低流阻, 良好的回弹性 (当受到挤压或者弯曲时, 迅速恢复原状), 弯曲极其灵活; 备有符合食品级要求的软管供选用。

应用范围: 室内泳池维护设备、吸排设备、纺织机械, 粒状物料输送。

温度范围: -50°C - +60°C

管壁标准色: 蓝色

Profile hoses

Structure: EVA.

Characteristics: An inside smooth full plastic profile hose with low flow resistance, good resilience (when compressed or bent) and excellent flexibility; also available in a food-proof version.

Applications: Swimming bath maintenance, suction equipment, textile machinery, granulate transport.

Temperature range: -50°C to +60°C

Colour: blue

内径 $\varnothing = d$		外径 $\varnothing = D$		弯曲半径	重量	≈ 负荷能力		长度	产品代码
I.D. $\varnothing = d$		O.D. $\varnothing = D$		r (min.)	Weight	≈ Load Capacity		Length	Part-No.
毫米 mm	公差 Tolerance	毫米 mm	公差 Tolerance	毫米 mm	克/米 g/m	负压 Vacuum mbar	压力 pressure bar	米 m	
25		33,0		50	220	600	0,6		74 1221 025 000
32		40,5		70	320	500	0,5		74 1221 032 000
35		43,6		75	350	500	0,5		74 1221 035 000
36		44,7		75	355	500	0,5		74 1221 036 000
37	±0,7	45,1	±1,0	80	360	500	0,5		74 1221 037 000
38		48,0		80	365	400	0,4		74 1221 038 000
40		50,0		90	380	400	0,4		74 1221 040 000
45		55,0		100	430	300	0,3		74 1221 045 000
50		61,0		120	510	250	0,25		74 1221 050 000
60		72,0		140	620	200	0,2		74 1221 060 000
70		81,0		165	720	170	0,17		74 1221 070 000
75	±1,0	87,0	±1,3	180	740	160	0,16		74 1221 075 000
76		88,0		180	750	160	0,16		74 1221 076 000
80		92,0		200	790	150	0,15		74 1221 080 000

如需其他内径和管壁颜色, 欢迎来电垂询

Other diameters and colours on request

表中负压和压力值会随安装和工作条件而改变。如有疑问, 请将应用告知我们, 我们非常高兴提供建议给您。如需其他规格软管 (如: 其他的内径、管壁颜色和公差), 欢迎来电垂询。

注: 以上数据基于常温 20°C。

Stand: 04/2003

Depending on installation or operating conditions, the vacuum or pressure values may differ from those stated in the table. In doubtful cases, provide a description of the application you have in mind, and we will be pleased to advise you. Alternative sizes and colours, different tolerances etc. can be supplied on request. Technical Data (at 20°C).